DC-50T



The DC-50T ia a 5" full-range ceiling speaker, which has a high sensitivity.

The DC-50T has a width frequency response.

The enclosure is halogen free and has low resonance.

The transformer allows it to be connected to 70 or 100V lines.

It is easy to install by means of the torsion springs.

Features:

• High performance: 92 dB (1W, 1m)

· Hight quality for music and voice playback

• Low loss transformer for 70 / 100V lines

· Easy intallation and low weight

Metallic grille: transparent acoustically

• External diameter: 189mm

TECHNICAL SPECIFICATIONS	
NOMINAL POWER	10W RMS
FREQUENCY RESPONSE	100Hz- 17.5 kHz (+/- 5 dB)
SENSITIVITY	92dB (1W, 1m)
SPEAKER IMPEDANCE	8 Ω
DISPERSION	Conical: 105° (@2 kHz)
COLOUR	White, RAL 9016
TRANSFORMER (70/100V)	10 / 5 / 2.5 / 1.25 W @ 100V 5 / 2.5 / 1.25 / 0.625 W @ 70V
CONNECTOR	Mate'n lock
FIXING	Torsion springs
DIMENSIONS (diameter x depth)	189 x 110 mm
CUT-OUT (diameter)	160mm
WEIGHT	1 kg



Telephone: +34 952028805 / Fax: +34 952020598 lda@lda.es / www.lda.es