





The EZ-407 of LDA is a column speaker which has high performance for professional installations.

It is designed to be installed on walls or columns and integrated with the environment due to its stylized design. The IP protection degree is IP-54 allowing the installation to anywhere – Indoor or Outdoor.

Furthermore, high fidelity is possible due to 4×1.5 " drivers and 1×1.5 tweeter integrated in it. The power selector allows the selection among 5-10-15W power for 100V lines.

The frequency range is contained from 250 Hz to 20 kHz.

Applications:

Public Address and Sound System Stations Airports Commercial Centres Fair and congress Centres

TECHNICAL SPECIFICATIONS	
NOMINAL POWER	20 W RMS
NOMINAL IMPEDANCE OF DRIVER	8 Ω
FREQUENCY RESPONSE	250 Hz- 20 kHz
SENSITIVITY	94 dB (1W,1m)
GRILLE	Metallic grille acoustically transparent (RAL 9010)
COVER	Aluminium
COLOUR	White RAL 9010
DISPERSION	111° Horizontally; 33° Vertically
TRANSFORMER (70/100V)	5/10/20 W @ 100V
INPUT LINE	100 V
DRIVER	4 x 1.5" driver and 1 x tweeter
IP PROTECTION	IP 54 (Waterproof and UV-resistant)
TEMPERATURE RANGE	-25°C - 70°C
DIMENSIONS (height x width x depth)	396 x 69.5 x 65 mm
WEIGHT	1.9 kg



Parque Tecnológico de Andalucía Severo Ochoa Street, 31st Post Code: 29590 Málaga, SPAIN Telephone: +34 952028805 / Fax: +34 952020598 Ida@Ida.es / www.Ida.es