# PRO-15T



The Pro-15T is an multipurpose acoustic box.

The enclosure is made in ABS and for low resonance. The grill is transparent acoustically.

This acoustic box could be installed by different optional brackets that Could be fixed or adjustable.

The colour could be chosen of the RAL palette.

#### Features:

- High quality of music and voice playback.
- High performance: 87 dB (1W, 1 m)
- Full-range speaker of 130 mm (5") diameter made in polypropylene with double cone of polycarbonate.
- Low temperature transformer for 70V / 100 V lines.
- Transparent acoustically metallic grill (R1,5 t2)

# Applications:

- High quality for public address systems.
- Commercial centres.
- Environmental music

- Offices
- Garages, factories,
- Warehouses

#### **TECHNICAL SPECIFICATIONS**

MAXIMUM POWER	30 W RMS
FREQUENCY RESPONSE	70-12.000 Hz. (- 10 dB)
SENSITIVITY	87 dB (1 W, 1 m)
SPEAKER IMPEDANCE	8 ohm
DISPERSION	Conical: 90°
TRANSFORMER (70V)	20, 10, 5, 2.5 W
PEAK SPL	109 dB
BRACKET (optional)	Shape: U. It could be fixed or adjustable.
DIMENSIONS (height x width x depth)	250 x 194 x 120 mm.
WEIGHT	2,4 kg.



# **PRO-15T**

# Installation requirements:


### **Bracket for mounting**

### Bracket fixed on ceiling



There are two heights for brackets: 164 mm y 533 mm.

\* The height could be modified if it is required.






# PRO-15T

# **Installations requirements:**

#### **ADJUSTABLE BRACKET**



+/- 180° vertical turn

+/- 180° horizontal turn

The Bracket is fixed on the ceiling through screws.

The relative turn between the box and the wall is over +/- 180°. The turn could be in vertical or horizontal direction.

#### **FIXED BRACKET. U SHAPE**



The bracket is fixed on the ceiling or wall by screws. This installing is possible due to the bracket contains drills in its bigger wing.

